



- 1 CV: Slotted hexagonal head bolts**  
DN 50 – DN 300: SW 10  
**CE: Hexagonal head bolts**  
DN 50, 70, 75/80: SW 10  
DN 100 – DN 300: SW 13
- 2 Guide plate**
- 3 Threaded plate**
- 4 Collar**
- 5 Sealing sleeve**

## The proven standard collar

The DCS CV/CE collar has been proven in all kinds of standard drainage applications. The proven standard collar for non-pull-out connections.

### Materials


W1	W2	W3	W4	W5
	x		x	

- W2**
  - Material, Collar: AISI 430 Ti
- Type CV**
  - Material, Clamping unit: Steel, surface protected
  - Material, Sealing sleeve: EPDM
  - Material, Bolts: Steel, surface protected
- W5**
  - Material, Collar: AISI 304
- Type CE**
  - Material, Clamping unit: AISI 304
  - Material, Sealing sleeve: EPDM
  - Material, Bolts: Steel, surface protected

### Advantages at a glance

- Fast and easy installation
- Suitable for repair purposes

## Technical data & Ordering information



NORMACONNECT® DCS CV								
Designation	DN	A (mm)	B (mm)	D (mm)	L (mm)	Torque (Nm)	Bolt (mm)	W2 Product No.
CV DN 50	50	14	22.5	65	48	4-6	M 6	0242 8091 050
CV DN 70	70	14	22.5	85	48	4-6	M 6	0242 8092 070
CV DN 80	75/80	14	22.5	90	48	6-8	M 6	0242 8093 075
CV DN 100	100	18	22.5	115	54	10-12	M 8	0262 8303 100
CV DN 125	125	18	31	140	65	10-12	M 8	0262 8304 125
CV DN 150	150	18	31	170	65	10-12	M 8	0262 8305 150
CV DN 200	200	18	37	220	78	15-20	M 8	0262 8306 200
CV DN 250	250	18	37	286	78	15-20	M 8	0262 8307 250
CV DN 300	300	18	37	338	78	15-20	M 8	0262 8308 300

DCS CV is also available with a round hexagonal head bolt on request.

NORMACONNECT® DCS CE								
Designation	DN	A (mm)	B (mm)	D (mm)	L (mm)	Torque (Nm)	Bolt (mm)	W4 Product No.
CE DN 50	50	14	22.5	65	48	4-6	M 6	0242 8108 050
CE DN 70	70	14	22.5	85	48	4-6	M 6	0242 8109 070
CE DN 100	100	18	22.5	115	54	10-12	M 8	0262 8361 100
CE DN 125	125	18	31	140	65	10-12	M 8	0262 8362 125
CE DN 150	150	18	31	170	65	10-12	M 8	0262 8363 150
CE DN 200	200	18	37	220	78	15-20	M 8	0262 8364 200
CE DN 250	250	18	37	286	78	15-20	M 8	0262 8365 250
CE DN 300	300	18	37	338	78	15-20	M 8	0262 8366 300

DCS CE is also available with a round hexagonal head bolt on request.